Electromagnetic · clinical use

Electromagnetic Shockwave Therapy System

A high-voltage coil generates a magnetic field; electromagnetic induction drives a metal diaphragm to produce the shockwave.



Key features

- Multi-level settings, flexible parameters
- Hi-res touch screen operation
- Simple operation, comfortable in use
- Compliant medical device qualification

SHANGLIJIA 尚利嘉
HUIZHOU SHANGLIJIA TECHNOLOGY CO., LTD.
WhatsApp +86 180 2799 8502 · shanglijia.pages.dev
jiayuhuang262010@gmail.com · Heyuan, Guangdong, China

Key features

- Multi-level settings, flexible parameters
- Hi-res touch screen operation
- Simple operation, comfortable in use
- Compliant medical device qualification
- 0-10 energy range: intensity and depth adjustable
- Adjustable water cushion controls treatment depth
- Ergonomic handpiece

Scope of application

Adjuvant therapy for periarthritis of the shoulder and tennis elbow

Specifications

Weight	14.5 kg
Body dimensions	405 x 357 x 191 mm
Shockwave generation	Electromagnetic
Focal distance from source	65 mm
Compressive peak pressure	30 MPa
Expansive peak pressure	15 MPa
Pulse width	<= 2 us
Distance from source axis	75 mm

SHANGLIJIA 尚利嘉

HUIZHOU SHANGLIJIA TECHNOLOGY CO., LTD.

WhatsApp +86 180 2799 8502 · **shanglijia.pages.dev**

jiayuhuang262010@gmail.com · Heyuan, Guangdong, China